Product Specifications
Burrows Concrete LTD

Code	Name/Description	Dimensions	Capacity/ M3	weight In KG's	Reinforcing and Ancillary	Stock Item or made to order	centre Concrete material
6r	600 Soak Ring	500mm I/D x 450mm High	0.0883	45	5mm wire top and bottom with 2 wire handles	Stock	Pumice
6l	600 Standard Soak ring lid	600mm O/D x 50mm thick	NA	35	665 Mesh. No handles	Stock	Concrete
9r	900 Soak Ring	900mm I/D x 450mm High	0.2861	115	5mm wire top and bottom with 2 wire handles	Stock	Pumice
9l	900 Standard soak Ring Lid	1050mm O/D x 90mm High	NA	150	665 Mesh with 2 Wire Handles	Stock	Concrete
9x9	900x900 Soak Ring	900mm I/D x 900mm High	0.5722	250	5mm wire top and bottom with 2 wire handles	Stock	Pumice
12r	1200 Soak Ring	1200mmI/D x 500mm High	0.5652	160	2 x 5mm wire top and bottom with 2 wire handles	Stock	Pumice
12l	1200 Standard Soak Ring Lid	1350mm O/D x 90mm Thick	N/A	270	665 Mesh with Criss Cross D12 and 2 wire handles	Stock	Concrete
BC6	600 BC Solid Chip Soak Ring	500mm I/D x 450mm High	0.0883	65	5mm wire top and bottom with 2 wire handles	MTO	7mm Chip
BC9	900 BC Solid Chip Soak Ring	900mm I/D x 450mm High	0.2861	170	5mm wire top and bottom with 2 wire handles	MTO	7mm Chip
BC 9x9	900x900 BC Solid Chip Soak Ring	900mm I/D x 900mm High	0.5722	370	5mm wire top and bottom with 2 wire handles	MTO	7mm Chip
BC12	1200 BC Solid Chip Soak Ring	1200mmI/D x 500mm High	0.5652	350	2 x 5mm wire top and bottom with 2 wire handles	MTO	7mm Chip
6s	600 Solid Riser	500mm I/D x 450mm High	0.0883	85	5mm wire top and bottom with 2 wire handles	Stock	Concrete
9s	900 Solid Riser	900mm I/D x 450mm High	0.2861	212	5mm wire top and bottom with 2 wire handles	Stock	Concrete
9x9s	900x900 Solid Riser	900mm I/D x 900mm High	0.5722	470	5mm wire top and bottom with 2 wire handles	Stock	Concrete
12s	1200 Solid Riser	1200mmI/D x 500mm High	0.5652	450	2 x 5mm wire top and bottom with 2 wire handles	Stock	Concrete
9hl	900 Heavy Soak ring Lid	1050/D x150mm thick	N/A	280	665 Mesh with Criss Cross D12 and 2 wire handles	Stock	Concrete
12hl	1200 Heavy Soak Ring Lid	13500/D x 120mm Thick	N/A	500	665 Mesh with Criss Cross D12 and 2 wire handles	Stock	Concrete
9lh	900 Standard soak Ring Lid WithHo	1050mm O/D x 90mm High	N/A	150	665 Mesh with 2 Wire Handles, With 100mm Hole	Stock	Concrete
12lh	1200 STD Soak Ring Lid with Hole	1350mm O/D x 90mm Thick	N/A	270	665 Mesh with D12 and 2 wire handles & 100mm Hole	Stock	Concrete
9lmhs	900 Standard Manhole Lid	1050mm x 90mm Thick	N/A	140	665 Mesh with D12 and 2 wire handles & 540mm Hole	Stock	Concrete
12lmhs	1200 Standard Manhole Lid	1350 x 90mm Thick	N/A	260	665 Mesh with D12 and 2 wire handles & 540mm Hole	Stock	Concrete
9hmhl	900 Heavy Manhole Lid	1050mm x 150mm Thick	N/A	260	665 Mesh with D12 and 2 wire handles & 540mm Hole	Stock	Concrete
12hmhl	1200 Heavy Manhole Lid	1350 x 120mm Thick	N/A	480	665 Mesh with D12 and 2 wire handles & 540mm Hole	Stock	Concrete
off	Offal Lid With Bung	1350mm O/D x 90mm Thick	N/A	270	665 Mesh with D12 and 2 wire handles & 440mm Hole	Stock	Concrete